

Product Description



Application range

- Used for computer systems, MSR technology, office machinery, scales - screened cables with small dimensions.
- Dry and damp indoors

Design

- Bare copper wire stranded conductor
- PVC core insulation and outer sheath
- tinned copper braid
- Colour: pebble grey (RAL 7032)

Product features

- Colour code in accordance with DIN 47100
- Flame retardant according to IEC 60332-1-2

Technical Data
Core identification code

DIN 47100 without colour repetition, see Appendix T9

Mutual capacitance

C/C approx. 120 nF/km C/S: approx. 160 nF/km

Peak working voltage

(not for power applications) 250 V

Inductivity

approx. 0.65 mH/km

Based on

VDE 0812

Specific insulation resistance

> 20 GOhm x cm

Conductor stranding

Strand, fine wire 0.34 mm², 7 wire

Conductor resistance

see Appendix T11

Minimum bending radius

For flexible applications: 15 x cable diameter fixed installation: 6 x cable diameter

Test voltage

At 0.14 mm²: 1200 V

> 0.14 mm²: 1500 V

Range of temperature

Fixed installation: -40°C up to +80°C

Flexing: -5°C up to +70°C

Article List

Part number	Number of cores and mm ² per conductor	Outer diameter in mm approx.	Copper index kg/km	Weight kg/km approx.
UNITRONIC® LiYCY				
0034302	2 x 0,14	3.9	12	20
0034303	3 x 0,14	4.1	13	28
0034304	4 x 0,14	4.3	14.3	33
0034305	5 x 0,14	4.6	15.5	38
0034306	6 x 0,14	4.9	18.2	38
0034307	7 x 0,14	4.9	19	49
0034308	8 x 0,14	5.8	21.2	56
0034310	10 x 0,14	6.1	28.5	66
0034312	12 x 0,14	6.3	30.4	78
0034314	14 x 0,14	6.7	32	80
0034315	15 x 0,14	6.9	37.8	86
0034316	16 x 0,14	7	43	90
0034318	18 x 0,14	7.3	48.8	104
0034320	20 x 0,14	7.7	53.9	116
0034321	21 x 0,14	7.9	55.5	121
0034325	25 x 0,14	8.4	63	149
0034328	28 x 0,14	8.5	66.1	153



0034330	30 x 0,14	8.7	69	158
0034332	32 x 0,14	9	73.6	164
0034336	36 x 0,14	9.3	83	183
0034340	40 x 0,14	10.4	87.5	210
0034344	44 x 0,14	10.7	110.5	225
0034350	50 x 0,14	11.1	122.5	253
0034402	2 x 0,25	4.5	16	32
0034403	3 x 0,25	4.7	21	37
0034404	4 x 0,25	5	24	41.3
0034405	5 x 0,25	5.6	29	51.2
0034406	6 x 0,25	6	30	58
0034407	7 x 0,25	6	37	65
0034408	8 x 0,25	7.1	42	73
0034410	10 x 0,25	7.5	46	82
0034412	12 x 0,25	7.7	53	145
0034414	14 x 0,25	8	59	99
0034415	15 x 0,25	8.3	61	111
0034416	16 x 0,25	8.4	64	124
0034418	18 x 0,25	8.8	83	143
0034420	20 x 0,25	9.3	88	152.3
0034421	21 x 0,25	9.6	93	161
0034425	25 x 0,25	10.7	114	172
0034428	28 x 0,25	10.8	126	181.1
0034430	30 x 0,25	11	132	189
0034432	32 x 0,25	11.4	138	203
0034436	36 x 0,25	11.8	148	220
0034440	40 x 0,25	12.7	157	248
0034450	50 x 0,25	13.8	178	318
0034461	61 x 0,25	15	205	365.2
0034502	2 x 0,34	4.9	21	37
0034503	3 x 0,34	5.1	27	49
0034504	4 x 0,34	5.7	28	59
0034505	5 x 0,34	6.2	30	66
0034506	6 x 0,34	6.8	45	79
0034507	7 x 0,34	6.8	48	83
0034508	8 x 0,34	7.8	52	94
0034510	10 x 0,34	8.3	74	129.2
0034512	12 x 0,34	8.5	80	142
0034514	14 x 0,34	8.9	86	154
0034515	15 x 0,34	9.2	90	155
0034516	16 x 0,34	9.4	94	160

0034518	18 x 0,34	10.2	103	173
0034520	20 x 0,34	10.7	112	192
0034521	21 x 0,34	11.1	116	199.2
0034525	25 x 0,34	11.9	135	259
0034528	28 x 0,34	12	153	280
0034530	30 x 0,34	12.3	159	291.1
0034532	32 x 0,34	13	165	305
0034536	36 x 0,34	13.4	179	331
0034540	40 x 0,34	14.8	200	365
0034550	50 x 0,34	15.9	235	431
0034602	2 x 0,5	5.6	29	54
0034603	3 x 0,5	5.9	38	67
0034604	4 x 0,5	6.3	43	77
0034605	5 x 0,5	7	51	90
0034606	6 x 0,5	7.6	59	104
0034607	7 x 0,5	7.6	65	112
0034608	8 x 0,5	8.7	70	135
0034610	10 x 0,5	9.3	88	160
0034612	12 x 0,5	9.6	99	177
0034618	18 x 0,5	11.8	134	239
0034620	20 x 0,5	12.1	149	276
0034625	25 x 0,5	13.7	211	352
0034630	30 x 0,5	14.5	230	397
0034702	2 x 0,75	6	38	64
0034703	3 x 0,75	6.3	49	76
0034704	4 x 0,75	7	58	92
0034705	5 x 0,75	7.6	67	109
0034707	7 x 0,75	8.2	100	156
0034710	10 x 0,75	10.5	130	187
0034712	12 x 0,75	10.8	154	218
0034718	18 x 0,75	13	195	327
0034725	25 x 0,75	15.3	280	454
0034730	30 x 0,75	15.8	312	486
0034802	2 x 1	6.3	43	72
0034803	3 x 1	6.8	56	90
0034804	4 x 1	7.3	68	109
0034805	5 x 1	8	79	126
0034807	7 x 1	8.6	118	171
0034810	10 x 1	11.1	140	228
0034812	12 x 1	11.4	168	259
0034818	18 x 1	13.4	252	389



0034825	25 x 1	16.2	335	517
0034902	2 x 1,5	7.5	58	90
0034903	3 x 1,5	7.9	74	115
0034904	4 x 1,5	8.5	108	153
0034905	5 x 1,5	9.3	129	176
0034907	7 x 1,5	10.5	164	220
0034912	12 x 1,5	13.7	254	376
0034918	18 x 1,5	16.3	350	519
0034925	25 x 1,5	19.9	550	901

Footnote:

Copper price basis: EUR 150 / 100 kg

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: Coil